


heat ex-changer coil fixing support use
fully stainless steel fixed clamp frame

EASYKIT
EasyKit Kit.
8096 Sukoró, Rákóczi utca 12.
26199784-2-07



Technical remarks:

1. The water tank is a pressurized thermal insulation hot & cold water tank.
2. The outer shell material is $\delta=0.5$ galvanized steel with white color painting sheet, black color caps. Insulation material is polyurethane foaming, tank side insulation thickness is 50mm, bottom & top side insulation thickness 50mm.
3. DHW 400L inner tank material is SUS316L stainless steel $\delta=1.8$ mm, built-in heat ex-changer wave stainless steel SUS316L coil $\Phi 32 \times 30$ m. Buffer tank 80L inner tank material is SUS304 stainless steel $\delta=1.8$ mm.
4. The tank test pressure is 1.0MPa, max. working pressure is 1.0MPa, suggested working pressure is 0.6MPa.
5. The surface of tank shell is clean, bright, no scratches, no pinholes, no bubbles and no defects.

						Combined tank 400I+80I		图纸编号	
标记 处数 分区 更改文件号 签字 日期						stainless steel SUS304		版本	页面
设计						$\delta=1.5$ mm		A	2/4
校对						outer shell		white color $\delta=0.5$ mm	
工艺						20230324		广州和瑞节能科技有限公司	
标准化								Guangzhou Herui Energy Saving Technology Co., Ltd.	
								比例	1:1